

PIVOT DOOR

with Optional Side Panel



1850
MM
HEIGHT
STANDARD RANGE

6
MM
GLASS
THICKNESS

5 YEARS
GUARANTEE

FEATURES & BENEFITS

- Height 1850mm
- 6mm Toughened Safety Glass
- Easy Clean Frame
- Reversible
- Chrome Handle
- 5yr Guarantee



Slot & Lock
Frame System
- No Screws




No Drilling
on Frame



Click on
Rollers



Assembled
on Tray



A: Door Opening

B: Door Swing

Easy Pivot Door

Size	Code	Recess Adjustment (Min-Max)	Side Panel Adjustment (Min-Max)	A	B
760	KBP76	710-750	715-735	515	525
800	KBP80	750-790	755-775	535	545
900	KBP90	850-890	855-875	605	615

Optional Side Panel

Size	Code	Side Panel Adjustment (Min-Max)
760	KBSP76	722-742
800	KBSP80	762-782
900	KBSP90	862-882

Please add 20mm to Tray Finish Adjustment when using a Side Panel.
For wetroom installation, please reduce Side Panel Tray Finish Adjustment by 20mm.
Inline panels can be fitted to either or both sides of sliding door.

SLIDING DOOR

with Optional Side Panel



1850
MM
HEIGHT
STANDARD RANGE

6
MM
GLASS
THICKNESS

5 YEARS
GUARANTEE

FEATURES & BENEFITS

- Height 1850mm
- 6mm Toughened Safety Glass
- Easy Clean Frame
- Reversible
- Chrome Handle
- 5yr Guarantee



Slot & Lock
Frame System
- No Screws




No Drilling
on Frame



Click on
Rollers



Assembled
on Tray



A: Door Opening

B: Fixed Panel

Easy Sliding Door

Size	Code	Recess Adjustment (Min-Max)	Side Panel Adjustment (Min-Max)	A	B
1000	KBS10	950-990	960-1000	375	435
1100	KBS11	1050-1090	1060-1100	425	485
1200	KBS12	1150-1190	1160-1200	475	535

Optional Side Panel

Size	Code	Side Panel Adjustment (Min-Max)
760	KBSP76	730-750
800	KBSP80	770-790
900	KBSP90	870-890

Please add 20mm to Tray Finish Adjustment when using a Side Panel.
For wetroom installation, please reduce Side Panel Tray Finish Adjustment by 20mm.
Inline panels can be fitted to either or both sides of sliding door.

BIFOLD DOOR

with Optional Side Panel



↑ 1850
MM
HEIGHT
STANDARD RANGE

6^{MM}
GLASS
THICKNESS

5 YEARS
GUARANTEE

FEATURES & BENEFITS

- Height 1850mm
- 6mm Toughened Safety Glass
- Easy Clean Frame
- Reversible
- Chrome Handle
- 5yr Guarantee



Slot & Lock
Frame System
- No Screws




No Drilling
on Frame



Click on
Rollers



Assembled
on Tray



A: Door Opening

B: Door Swing

Easy Bifold Door

Size	Code	Recess Adjustment (Min-Max)	Side Panel Adjustment (Min-Max)	A	B
700	KBB70	660-690	655-675	400	305
760	KBB76	710-750	715-735	450	335
800	KBB80	750-790	755-775	480	355
900	KBB90	850-890	855-875	560	400

Optional Side Panel

Size	Code	Side Panel Adjustment (Min-Max)
760	KBSP76	730-750
800	KBSP80	770-790
900	KBSP90	870-890

Please add 20mm to Tray Finish Adjustment when using a Side Panel.
For wetroom installation, please reduce Side Panel Tray Finish Adjustment by 20mm.
Inline panels can be fitted to either or both sides of sliding door.

2 DOOR QUADRANT



1850
MM
HEIGHT
STANDARD RANGE

6
MM
GLASS
THICKNESS

5 YEARS
GUARANTEE

FEATURES & BENEFITS

- Height 1850mm
- 6mm Toughened Safety Glass
- Easy Clean Frame
- Reversible
- Chrome Handle
- 5yr Guarantee



Slot & Lock
Frame System
- No Screws




No Drilling
on Frame



Click on
Rollers



Assembled
on Tray



A = Door Opening
B = Flat Fixed Panel
C = Flat Fixed Panel

Easy 2 Door Quadrant

Size	Code	Recess Adjustment (Min-Max)	A	B	C
800	KB2Q108	770-790	470	425	225
900	KB2Q128	870-890	470	625	225

Easy 2 Door Offset Quadrant

Size	Code	Side Panel Adjustment (Min-Max)	A	B	C
1000X800	KB2Q108	970-990/ 770-790	470	425	225
1200X800	KB2Q128	1170-1190/ 770-790	470	625	225
1200X900	KB2Q129	1170-1190/ 870-890	545	625	325

Please add 20mm to Tray Finish Adjustment when using a Side Panel.
For wetroom installation, please reduce Side Panel Tray Finish Adjustment by 20mm.
Inline panels can be fitted to either or both sides of sliding door.

CORNER DOOR

with Optional Side Panel



↑ 1850
MM
HEIGHT
STANDARD RANGE

6^{MM}
GLASS
THICKNESS

5 YEARS
GUARANTEE

FEATURES & BENEFITS

- Height 1850mm
- 6mm Toughened Safety Glass
- Easy Clean Frame
- Reversible
- Chrome Handle
- 5yr Guarantee



Slot & Lock
Frame System
- No Screws




No Drilling
on Frame



Click on
Rollers



Assembled
on Tray



A = Door Opening
B = Flat Fixed Panel
C = Flat Fixed Panel

Easy Corner Door

Size	Code	Recess Adjustment (Min-Max)	A	B
800	KBC80	770-790	400	395
900	KBC90	870-890	480	445